

# MOTO 4T 10W40

## Description

Semi-synthetic, four-stroke, motorcycle oil. It offers optimum clutch performance, high lubricity and gearbox wear protection.

## Application

ROVEL 4T 10W-40 is an advanced lubricant designed for modern motorcycle engines and large-sized scooters. It is suitable for all seasons.

## Operation Characteristics

- Reliable operation and efficiency in all modern engines.
- Excellent performance even in the toughest conditions.
- Excellent cold starting and rapid oil circulation.
- Excellent protection against wear and excellent lubrication.
- High oxidation stability.
- Optimum clutch performance.
- Compatible with all gaskets and sealants.
- Gearbox wear protection.

## Specifications, Approvals, Recommendations

API SL/ CF

## Typical Physical Characteristics

|                          | ASTM   | 10W-40 |
|--------------------------|--------|--------|
| DENSITY (kg/ltr)         | D 1298 | 0,871  |
| VISCOSITY AT 40°C (cSt)  | D 445  | 96,5   |
| VISCOSITY AT 100°C (cSt) | D 445  | 14,5   |
| VISCOSITY INDEX          | D 2270 | 156    |
| FLASH POINT (°C ) min.   | D 92   | 220    |
| POUR POINT (°C)          | D 97   | -33    |
| CCS @ -25 C              | D-5293 | 5950   |

*These are typical values. Small variation should be expected for future productions / blendings*

## Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.