

MOTO 4T ML 20W50

Description

High quality, multi-grade, four-stroke motorcycle oil. It offers engine protection and reliable clutch performance.

Application

MOTO 4T ML 20W-50 is an advanced lubricant designed for modern motorcycles and scooters equipped with four stroke engines.

Operation Characteristics

- Protect metal parts from corrosion and rust
- Resistance to oxidation at high temperatures
- High resistance to wear
- Excellent deposit control
- Very good emission control

Specifications, Approvals, Recommendations

API SJ, JASO MA2

Typical Physical Characteristics

	ASTM	20W-50
SPECIFIC GRAVITY (kg/ltr)	D 1298	0,888
VISCOSITY AT 40°C (cSt)	D 445	165
VISCOSITY AT 100°C (cSt)	D 445	18,5
VISCOSITY INDEX	D 2270	126
FLASH POINT (°C) min.	D 92	240
POUR POINT (°C)	D 97	-24

These are typical values. Small variation should be expected for future productions / blendings

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.