

ATF 3000 DEX III

Description

High viscosity index, synthetic transmission fluid suitable for most automatic transmissions, clutches and steering systems in passenger cars, commercial trucks and off-road machinery. It offers smooth performance and oxidation stability.

Application

ROVEL ATF 3000 DEX III is suitable for automatic transmissions, torque converters, power steering systems, power transmissions, industrial and hydraulic clutches.

Operation Characteristics

- Optimum torque converter operation.
- Wide temperature range.
- Excellent wear protection of gears, pumps and thrust bearings.
- Excellent performance at low and high temperatures.
- Excellent anticorrosion and antirust properties.
- Very good performance for long-term mechanical stress.
- Does not affect elastomers and non-ferrous metals like copper or alloys.

Specifications, Approvals, Recommendations

GM DEXRON III G/H, ALLISON C-4, MERCON, VOITH G 607, MB 236.9, ZF-TE-ML 14

Typical Physical Characteristics

	ASTM	DIII
SPECIFIC GRAVITY (kg/l)	D 1298	0,865
VISCOSITY AT 40°C (cSt)	D 445	34
VISCOSITY AT 100°C (cSt)	D 445	7,3
VISCOSITY INDEX	D 2270	188
FLASH POINT (°C) min.	D 92	200
POUR POINT (°C)	D 97	-45
COLOUR		RED

These are typical values. Small variation should be expected for future productions / blendings

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.