

# ATF 3000tt DEX III

## Description

High viscosity index, synthetic transmission fluid suitable for most automatic transmissions, including tip-tronic. It offers smooth performance and oxidation stability.

## Application

ROVEL TF 3000 tt DEX III is suitable for automatic transmissions of passenger cars, tip-tronic transmissions, torque converters and power transmission systems of heavy duty vehicles.

## Operation Characteristics

- Optimum torque converter operation.
- Wide temperature range.
- Excellent wear protection of gears, pumps and thrust bearings.
- Excellent performance at low and high temperatures.
- Excellent anticorrosion and antirust properties.
- Very good performance for long-term mechanical stress.
- Does not affect elastomers and non-ferrous metals like copper or alloys.

## Specifications, Approvals, Recommendations

GM DEXRON IIIIG/H, ALLISON C-4, MERCON, VOITH G 607, MB 236.9, ZF-TE-ML 14

## Typical Physical Characteristics

	<b>ASTM</b>	<b>DIII</b>
<b>SPECIFIC GRAVITY (kg/l)</b>	D 1298	0,865
<b>VISCOSITY AT 40°C (cSt)</b>	D 445	34
<b>VISCOSITY AT 100°C (cSt)</b>	D 445	7,3
<b>VISCOSITY INDEX</b>	D 2270	188
<b>FLASH POINT (°C ) min.</b>	D 92	200
<b>POUR POINT (°C)</b>	D 97	-45
<b>COLOUR</b>		WHITE

*These are typical values. Small variation should be expected for future productions / blendings*

## Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.