

CHROME FS 5W40

Description

High performance synthetic engine oil for passenger cars and light commercial vehicles offering optimum anti wear protection and engine cleansing for extended oil drain intervals.

Application

ROVEL CHROME FS 5W-40 is an advanced synthetic lubricant, designed for gasoline and diesel engines of passenger cars and light trucks without DPF. It provides fuel economy and reduced emissions.

Operation Characteristics

- Superior soot and sludge handling.
- Excellent cold starting and rapid oil circulation to minimize engine wear
- Reduced fuel consumption and reduced emissions
- Optimum anti-wear protection.
- Compatible with all gaskets and sealants.
- Minimum oil consumption.

Specifications, Approvals, Recommendations

API SN/CF, ACEA A3/B4, MB 229.3, VW 501.01/502.00/505.00, BMW LL-01, OPEL GM-LL-B-025, RENAULT RN 0700/0710

Typical Physical Characteristics

	ASTM	5W-40
SPECIFIC GRAVITY (kg/l)	D 1298	0,875
VISCOSITY AT 40°C (cSt)	D 445	88
VISCOSITY AT 100°C (cSt)	D 445	14,2
VISCOSITY INDEX	D 2270	167
TBN	D 2896	10
FLASH POINT (°C) min.	D 92	220
POUR POINT (°C)	D 97	-36

These are typical values. Small variation should be expected for future productions / blendings

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.