

SHIFT VRT 75W80

Description

Semi-synthetic manual transmission lubricant, designed to offer excellent wear protection, EP performance and fuel economy for long drain intervals.

Application

SHIFT VRT 75 W-80 is designed for use in the PSA group gearboxes.

Operation Characteristics

- Reliable operation under high loads in manual gearboxes
- Prevents reliably from wear, creating sludge and oxidation
- Reliable operation in all temperatures
- Superior bearing and gear protection
- Excellent performance at low temperatures.

Specifications, Approvals, Recommendations

API GL-4/GL-5/MT 1 MIL-L-2105 C&D, PSA (Peugeot, Citroen).

Typical Physical Characteristics

	ASTM	75W-80
SPECIFIC GRAVITY (kg/ltr)	D 1298	0,880
VISCOSITY AT 40°C (cSt)	D 445	75,8
VISCOSITY AT 100°C (cSt)	D 445	10,9
VISCOSITY INDEX	D 2270	132
FLASH POINT (°C) min.	D 92	215
POUR POINT (°C)	D 97	-33

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.

ROVEL Lubricants are designed, produced and distributed in accordance with a Certified Management System as per ISO9001, ISO14001 and OHSAS 18001 requirements
Issue Date : September 2017